Walvoline.	Page: 1
SAFETY DATA SHEET	Revision Date: 07/10/2017
	Print Date: 9/8/2017
	SDS Number: R0170829
PARTS Master® SAE 10W-30 Motor Oil	Version: 1.5
PM5129	

29 CFR 1910.1200 (OSHA HazCom 2012)
SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name

PARTS Master® SAE 10W-30

Motor Oil

Details of the supplier of the safety data sheet

Valvoline LLC 100 Valvoline Way Lexington, KY 40509 United States of America (USA) 1-800-TEAMVAL (1-800-8326-825) Emergency telephone number 1-800-VALVOLINE (1-800-825-8654)

Regulatory Information Number 1-800-TEAMVAL (1-800-8326-825)

Product Information

1-800-TEAMVAL (1-800-8326-825)

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

This material is considered hazardous under the OSHA Hazard Communication Standard criteria, based on hazard(s) not otherwise classified.

GHS label elements

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

Other hazards

Static-accumulating flammable liquid.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture

: Mixture

Chemical nature

; Defatter

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	Asp. Tox. 1; H304	3.36
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	Asp. Tox. 1; H304	3,226
Lubricating oils (petroleum),	64742-58-1	This material is	1.2513

Walvoline.	Page: 2
SAFETY DATA SHEET	Revision Date: 07/10/2017
	Print Date: 9/8/2017
	SDS Number: R0170829
PARTS Master® SAE 10W-30 Motor Oil	Version: 1.5
PM5129	

hydrotreated	considered hazardous under the OSHA Hazard Communication Standard criteria, based on hazard(s) not otherwise classified.	
--------------	--	--

SECTION 4. FIRST AID MEASURES

General advice

: No hazards which require special first aid measures.

If inhaled

: If breathed in, move person into fresh air.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact

: First aid is not normally required. However, it is

recommended that exposed areas be cleaned by washing

with soap and water.

In case of eye contact

: Remove contact lenses.

Protect unharmed eye.

If swallowed

: Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed

: Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:

acne

stomach or intestinal upset (nausea, vomiting, diarrhea)

irritation (nose, throat, airways)

W Valvoline	Page: 3
SAFETY DATA SHEET	Revision Date: 07/10/2017
ORIETT DATA OTHER	Print Date: 9/8/2017
	SDS Number: R0170829
PARTS Master® SAE 10W-30 Motor Oil	Version: 1.5
PM5129	

Notes to physician

: No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray

Foam

Carbon dioxide (CO2)

Dry chemical

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: carbon dioxide and carbon monoxide

Hydrocarbons

nitrogen oxides (NOx)

Specific extinguishing

methods

: Product is compatible with standard fire-fighting agents.

Product is compatible with standard fire-fighting agents.

Further information

: Standard procedure for chemical fires.

Standard procedure for chemical fires.

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

: Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions

: Prevent further leakage or spillage if safe to do so.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

Other information

: Comply with all applicable federal, state, and local regulations.

Valvoline	Page: 4
SAFETY DATA SHEET	Revision Date: 07/10/2017
	Print Date: 9/8/2017
	SDS Number: R0170829
PARTS Master® SAE 10W-30 Motor Oil	Version: 1.5
PM5129	

SECTION 7. HANDLING AND STORAGE

Advice on safe handling

: Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.

Materials to avoid

: No materials to be especially mentioned.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of	Control parameters / Permissible	Basis
		exposure)	concentration	
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	TWA	5 mg/m3 Mist	OSHA Z-1
.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL
Lubricating oils (petroleum), hydrotreated	64742-58-1	TWA	5 mg/m3 Inhalable fraction	ACGIH

Engineering measures

: General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Valvoline	Page: 5
SAFETY DATA SHEET	Revision Date: 07/10/2017
	Print Date: 9/8/2017
	SDS Number: R0170829
PARTS Master® SAE 10W-30 Motor Oil	Version: 1.5
PM5129	

Personal protective equipment

Respiratory protection

No personal respiratory protective equipment normally

required.

Eye protection

Not required under normal conditions of use. Wear splash-

proof safety goggles if material could be misted or splashed

into eyes.

Skin and body protection

Wear as appropriate:

Safety shoes

Wear resistant gloves (consult your safety equipment

supplier).

Hygiene measures

General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state

: liquid

Odour

: No data available

Odour Threshold

: No data available

рΗ

No data available

Melting point/freezing point

No data available

Boiling point/boiling range

: No data available

Flash point

: > 390 °F / > 199 °C

Method: Cleveland open cup

Evaporation rate

: No data available

Flammability (solid, gas)

: No data available

Flammability (liquids)

Flammability (liquids)

Static-accumulating flammable liquid.

Upper explosion limit

No data available

Lower explosion limit

: No data available

Vapour pressure

: 0.0133333 hPa (21.11 °C)

Valvoline.	Page: 6
SAFETY DATA SHEET	Revision Date: 07/10/2017
	Print Date: 9/8/2017
	SDS Number: R0170829
PARTS Master® SAE 10W-30 Motor Oil	Version: 1.5
PM5129	

Calculated Vapor Pressure

Relative vapour density

: No data available

Relative density

: No data available

Density

: 0.868 g/cm3 (15.56 °C)

Solubility(ies)

Water solubility

: No data available

Solubility in other solvents

: No data available

Partition coefficient: n-

octanol/water

: No data available

Thermal decomposition

No data available

Viscosity

Viscosity, dynamic

: No data available

Viscosity, kinematic

: 70 mm2/s (40 °C)

Oxidizing properties

: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity

: No decomposition if stored and applied as directed.

Chemical stability

: Stable under recommended storage conditions.

Possibility of hazardous

reactions

: Product will not undergo hazardous polymerization.

Conditions to avoid

; excessive heat

Incompatible materials

: Strong oxidizing agents

Hazardous decomposition

products

carbon dioxide and carbon monoxide Hydrocarbons

Nitrogen oxides (NOx)

SECTION 11. TOXICOLOGICAL INFORMATION

Valvoline	Page: 7
SAFETY DATA SHEET	Revision Date: 07/10/2017
	Print Date: 9/8/2017
	SDS Number: R0170829
PARTS Master® SAE 10W-30 Motor Oil	Version: 1.5
PM5129	

Information on likely routes of : Inhalation

exposure

Skin contact

Eye Contact Ingestion

Acute toxicity

Not classified based on available information.

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Acute oral toxicity

: LD50 (Rat): > 15 g/kg

Acute dermal toxicity

: LD50 (Rabbit): > 5 g/kg

Lubricating oils (petroleum), hydrotreated:

Acute oral toxicity

: LD50 (Rat): > 2,000 mg/kg

Assessment: Not classified as acutely toxic by ingestion under

Acute dermal toxicity

: LD50 (Rat): > 2,000 mg/kg

Assessment: Not classified as acutely toxic by dermal

absorption under GHS.

Skin corrosion/irritation

Not classified based on available information.

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Result: Slight, transient irritation

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result: Slight, transient irritation

Lubricating oils (petroleum), hydrotreated:

Result: No skin irritation

Result: Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Result: No eye irritation

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result: Slight, transient irritation

Lubricating oils (petroleum), hydrotreated:

W Valvoline.	Page: 8
SAFETY DATA SHEET	Revision Date: 07/10/2017
	Print Date: 9/8/2017
	SDS Number: R0170829
PARTS Master® SAE 10W-30 Motor Oil	Version: 1.5
PM5129	

Result: Slight, transient irritation

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic: May be fatal if swallowed and enters airways.

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

Carcinogenicity:

IARC

No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP

No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Valvoline	Page: 9
SAFETY DATA SHEET	Revision Date: 07/10/2017
	Print Date: 9/8/2017
	SDS Number: R0170829
PARTS Master® SAE 10W-30 Motor Oil	Version: 1.5
PM5129	

Acute aquatic toxicity

: Not classified based on available information.

Chronic aquatic toxicity

: Not classified based on available information.

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Toxicity to fish

: LL50 (Fish): > 100 mg/l

aquatic invertebrates

Toxicity to daphnia and other : EL50 (Aquatic invertebrates): > 10,000 mg/l

: EL50 (Algae, algal mat (Algae)): > 100 mg/l Toxicity to algae

Toxicity to fish (Chronic

toxicity)

: NOEC (Fish): 10 mg/l

aquatic invertebrates (Chronic toxicity)

Toxicity to daphnia and other : NOEC (Aquatic invertebrates): 10 mg/l

Lubricating oils (petroleum), hydrotreated:

Toxicity to daphnia and other : LC50 (Brine shrimp (Artemia salina)): > 22,500 mg/l

aquatic invertebrates Exposure time: 48 h

Ecotoxicology Assessment

Chronic aquatic toxicity

: No toxicity at the limit of solubility

Persistence and degradability

Components:

No data available

Bioaccumulative potential

Components:

No data available

Mobility in soil

Components:

No data available

Other adverse effects

No data available

Product:

Additional ecological

: No data available

information

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice

: Dispose of in accordance with all applicable local, state and

federal regulations.

Valvoine.	Page: 10
SAFETY DATA SHEET	Revision Date: 07/10/2017
	Print Date: 9/8/2017
	SDS Number: R0170829
PARTS Master® SAE 10W-30 Motor Oil	Version: 1.5
PM5129	

: Empty remaining contents. Contaminated packaging **SECTION 14. TRANSPORT INFORMATION** International transport regulations REGULATION **PACKING** MARINE PROPER SHIPPING NAME *HAZARD SUBSIDIARY ID NUMBER **GROUP** CLASS **HAZARDS** POLLUTANT / LTD. QTY. U.S. DOT - ROAD Not dangerous goods CFR_RAIL_C Not dangerous goods U.S. DOT - INLAND WATERWAYS Not dangerous goods TDG_ROAD_C Not dangerous goods TDG_RAIL_C Not dangerous goods TDG INWT C Not dangerous goods INTERNATIONAL MARITIME DANGEROUS GOODS Not dangerous goods INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO Not dangerous goods INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER Not dangerous goods MX DG Not dangerous goods

Valvoline	Page: 11
SAFETY DATA SHEET	Revision Date: 07/10/2017
	Print Date: 9/8/2017
	SDS Number: R0170829
PARTS Master® SAE 10W-30 Motor Oil	Version: 1.5
PM5129	

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

		~9
Marine pollutant	no	
	,	1

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
TOLUENE	108-88-3	1000	*

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards

: No SARA Hazards

SARA 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop 65

This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or other

reproductive harm.

The components of this product are reported in the following inventories:

TSCA

: On TSCA Inventory

DSL

: All components of this product are on the Canadian DSL

AICS

: On the inventory, or in compliance with the inventory

ENCS

: Contact your sales representative for additional information.

KECI

: On the inventory, or in compliance with the inventory

PICCS

: On the inventory, or in compliance with the inventory

IECSC

: Low volume exemption

IECSC

: q (quantity restricted)

Inventories


Valvoline	Page: 12
SAFETY DATA SHEET	Revision Date: 07/10/2017
OAI ETT BATA OTTEET	Print Date: 9/8/2017
	SDS Number: R0170829
PARTS Master® SAE 10W-30 Motor Oil	Version: 1.5
PM5129	

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 07/10/2017



NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements

H304

May be fatal if swallowed and enters airways.

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet:

ACGIH: American Conference of Industrial Hygienists

W. Valvoline.	Page: 13
SAFETY DATA SHEET	Revision Date: 07/10/2017
	Print Date: 9/8/2017
	SDS Number: R0170829
PARTS Master® SAE 10W-30 Motor Oil	Version: 1.5
PM5129	

BEI: Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx: Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

OEL: Occupational Exposure Limit P-Statement : Precautionary Statement PBT: Persistent, Bioaccumulative and Toxic

PPE: Personal Protective Equipment STEL: Short-term exposure limit STOT: Specific Target Organ Toxicity

TLV: Threshold Limit Value TWA: Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

DOT: Department of Transportation

FIFRA: Federal Insecticide, Fungicide, and Rodenticide Act HMIRC: Hazardous Materials Information Review Commission

HMIS: Hazardous Materials Identification System

NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health OSHA: Occupational Safety and Health Administration

PMRA: Health Canada Pest Management Regulatory Agency

RTK: Right to Know

WHMIS: Workplace Hazardous Materials Information System