

# SAFETY DATA SHEET



## A00141 MST STAINLESS STL CLNR/PLSH 20N15

Version 1.4

Revision Date 02/25/2017

Print Date 02/06/2018

### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : A00141 MST STAINLESS STL CLNR/PLSH 20N15

Material number : 000000000001001541

#### Manufacturer or supplier's details

Company : Zep Inc.

Address : 1310 Seaboard Industrial Blvd., NW  
Atlanta, GA 30318

Telephone : 404-352-1680

#### Emergency telephone numbers

**For SDS Information** : Compliance Services 1-877-428-9937

**For a Medical Emergency** : 877-541-2016 Toll Free - All Calls Recorded

**For a Transportation Emergency** : CHEMTREC: 800-424-9300 - All Calls Recorded.  
In the District of Columbia 202-483-7616

#### Recommended use of the chemical and restrictions on use

Recommended use : Cleaner

### SECTION 2. HAZARDS IDENTIFICATION

#### Emergency Overview

Appearance	Aerosol containing a liquefied gas
Colour	clear
Odour	characteristic

#### GHS Classification

Flammable aerosols : Category 1  
Gases under pressure : Liquefied gas  
Skin sensitisation : Category 1

#### GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.  
H280 Contains gas under pressure; may explode if heated.  
H317 May cause an allergic skin reaction.

Precautionary statements : **Prevention:**  
P210 Keep away from heat/sparks/open flames/hot surfaces.  
No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Pressurized container: Do not pierce or burn, even after

**A00141 MST STAINLESS STL CLNR/PLSH 20N15**

Version 1.4

Revision Date 02/25/2017

Print Date 02/06/2018

use.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves.

**Response:**

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P363 Wash contaminated clothing before reuse.

**Storage:**

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

**Disposal:**

Dispose of contents/container in accordance with local regulation.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Hazardous components**

Chemical name	CAS-No.	Concentration [%]
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>= 50 - < 70
Distillates (petroleum), hydrotreated light	64742-47-8	>= 20 - < 30
propane	74-98-6	>= 5 - < 10
butane	106-97-8	>= 5 - < 10
citral	5392-40-5	>= 0.1 - < 1

The exact percentages of disclosed substances are withheld as trade secrets.

**SECTION 4. FIRST AID MEASURES**

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : If unconscious place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician.  
Wash off immediately with plenty of water for at least 15 minutes.  
If on clothes, remove clothes.
- In case of eye contact : Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.  
If in eyes, rinse with water for 15 minutes.
- If swallowed : Keep respiratory tract clear.  
Never give anything by mouth to an unconscious person.

# SAFETY DATA SHEET



## A00141 MST STAINLESS STL CLNR/PLSH 20N15

Version 1.4

Revision Date 02/25/2017

Print Date 02/06/2018

If symptoms persist, call a physician.  
DO NOT induce vomiting unless directed to do so by a physician or poison control center.

Most important symptoms and effects, both acute and delayed : Effects are immediate and delayed.  
Symptoms may include irritation, redness, pain, and rash. Effects are dependent on exposure (dose, concentration, contact time).  
Causes skin irritation.  
May cause an allergic skin reaction.  
Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

---

### SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical  
Water spray jet

Unsuitable extinguishing media : High volume water jet

Hazardous combustion products : Carbon dioxide (CO<sub>2</sub>)  
Carbon monoxide  
Smoke

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Further information : For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Sweep up or vacuum up spillage and collect in suitable



**A00141 MST STAINLESS STL CLNR/PLSH 20N15**

Version 1.4

Revision Date 02/25/2017

Print Date 02/06/2018

container for disposal.

**SECTION 7. HANDLING AND STORAGE**

- Advice on safe handling** : Avoid exposure - obtain special instructions before use.  
 Avoid contact with skin and eyes.  
 For personal protection see section 8.  
 Smoking, eating and drinking should be prohibited in the application area.  
 Take precautionary measures against static discharges.  
 Provide sufficient air exchange and/or exhaust in work rooms.  
 Open drum carefully as content may be under pressure.  
 Dispose of rinse water in accordance with local and national regulations.  
 Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
 Always replace cap after use.  
 Do not breathe vapours or spray mist.
- Conditions for safe storage** : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.  
 No smoking.  
 Keep in a dry, cool and well-ventilated place.  
 Observe label precautions.  
 Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid** : Strong oxidizing agents

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Mist)	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m <sup>3</sup>	ACGIH
Distillates (petroleum), hydrotreated light	64742-47-8	TWA	500 ppm 2,000 mg/m <sup>3</sup>	OSHA Z-1
		TWA	400 ppm 1,600 mg/m <sup>3</sup>	OSHA P0
		TWA (Mist)	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Mist)	5 mg/m <sup>3</sup>	OSHA P0
		TWA (Mist)	5 mg/m <sup>3</sup>	NIOSH REL

**SAFETY DATA SHEET**



**A00141 MST STAINLESS STL CLNR/PLSH 20N15**

Version 1.4

Revision Date 02/25/2017

Print Date 02/06/2018

		ST (Mist)	10 mg/m3	NIOSH REL
		PEL (particulate)	5 mg/m3	CAL PEL
propane	74-98-6	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0
		PEL	1,000 ppm 1,800 mg/m3	CAL PEL
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		TWA	800 ppm 1,900 mg/m3	OSHA P0
		PEL	800 ppm 1,900 mg/m3	CAL PEL
citral	5392-40-5	TWA (Inhalable fraction and vapor)	5 ppm	ACGIH

**Engineering measures** : effective ventilation in all processing areas

**Personal protective equipment**

**Respiratory protection** : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

**Hand protection**

**Material** : Protective gloves  
**Remarks** : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

**Eye protection** : Safety glasses  
 Ensure that eyewash stations and safety showers are close to the workstation location.

**Skin and body protection** : Impervious clothing  
 Choose body protection according to the amount and concentration of the dangerous substance at the work place.

**Hygiene measures** : When using do not eat or drink.  
 When using do not smoke.  
 Wash hands before breaks and at the end of workday.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

**Appearance** : Aerosol containing a liquefied gas

**Colour** : clear

# SAFETY DATA SHEET



## A00141 MST STAINLESS STL CLNR/PLSH 20N15

Version 1.4

Revision Date 02/25/2017

Print Date 02/06/2018

Odour	: characteristic
Odour Threshold	: No data available
pH	: Not applicable
Melting point/freezing point	: Not applicable
Boiling point	: Not applicable
Flash point	: Not applicable
Evaporation rate	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol.
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: 4,136 hPa (21 °C)
Relative vapour density	: No data available
Density	: 0.856 g/cm <sup>3</sup>
Solubility(ies)	
Water solubility	: insoluble
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: not determined
Thermal decomposition	: No data available
Viscosity	
Viscosity, kinematic	: No data available
Heat of combustion	: 46.27 kJ/g

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	: Carbon oxides Smoke

# SAFETY DATA SHEET



## A00141 MST STAINLESS STL CLNR/PLSH20N15

Version 1.4

Revision Date 02/25/2017

Print Date 02/06/2018

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Potential Health Effects

Aggravated Medical Condition : None known.  
Symptoms of Overexposure : Effects are immediate and delayed.  
Symptoms may include irritation, redness, pain, and rash.  
Effects are dependent on exposure (dose, concentration, contact time).

#### Carcinogenicity:

**IARC** : No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.  
**OSHA** : No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.  
**NTP** : No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

#### Acute toxicity

##### Product:

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg  
Method: Calculation method

##### Components:

##### **Distillates (petroleum), hydrotreated heavy naphthenic:**

Acute oral toxicity : LD50 Rat: > 5,000 mg/kg

Acute inhalation toxicity : LC50 Rat: > 5 mg/l  
Exposure time: 4 h

Acute dermal toxicity : LD50 Rabbit: > 5,000 mg/kg

##### **Distillates (petroleum), hydrotreated light:**

Acute oral toxicity : LD50 Rat: > 5,000 mg/kg

Acute inhalation toxicity : LC50 Rat: > 4.6 mg/l  
Exposure time: 6 h

Acute dermal toxicity : LD50 Rat: > 2,000 mg/kg

##### **propane:**

Acute inhalation toxicity : LC50 Mouse: 1,237 mg/l  
Exposure time: 2 h



**SAFETY DATA SHEET**



**A00141 MST STAINLESS STL CLNR/PLSH 20N15**

Version 1.4

Revision Date 02/25/2017

Print Date 02/06/2018

LC50 Rat: 658 mg/l  
Exposure time: 4 h

LC50 Rat: 1,355 mg/l

**butane:**  
Acute inhalation toxicity : LC50 Mouse: 1,237 mg/l  
Exposure time: 2 h

LC50 Rat: 1,355 mg/l

**Skin corrosion/irritation**

**Product:**

Remarks: Irritating to skin.

**Serious eye damage/eye irritation**

**Product:**

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

**Respiratory or skin sensitisation**

**Product:**

Remarks: Causes sensitisation.

**Germ cell mutagenicity**

No data available

**Carcinogenicity**

No data available

**Reproductive toxicity**

No data available

**Distillates (petroleum), hydrotreated heavy naphthenic:**  
**Distillates (petroleum), hydrotreated light:**  
**propane:**  
**butane:**  
**citral:**

**STOT - single exposure**

No data available

**STOT - repeated exposure**

No data available

**Aspiration toxicity**

No data available

**Further information**



**SAFETY DATA SHEET**



**A00141 MST STAINLESS STL CLNR/PLSH 20N15**

Version 1.4

Revision Date 02/25/2017

Print Date 02/06/2018

**Product:**

Remarks: No data available

**Components:**

**Distillates (petroleum), hydrotreated light:**

Remarks: No data available

---

**SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**Bioaccumulative potential**

**Product:**

Partition coefficient: n-octanol/water : Remarks: No data available

**Components:**

**butane :**

Partition coefficient: n-octanol/water : Pow: 2.89

**citral :**

Partition coefficient: n-octanol/water : Pow: 2.76

**Mobility in soil**

No data available

**Other adverse effects**

No data available

**Product:**

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

**Components:**

**Distillates (petroleum), hydrotreated light :**

Additional ecological information : No data available

**SAFETY DATA SHEET**



**A00141 MST STAINLESS STL CLNR/PLSH 20N15**

Version 1.4

Revision Date 02/25/2017

Print Date 02/06/2018

---

**SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods**

- Waste from residues : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Dispose of in accordance with local regulations.
- Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

---

**SECTION 14. TRANSPORT INFORMATION**

Transportation Regulation: 49 CFR (USA):  
ORM-D, CONSUMER COMMODITY

Transportation Regulation: IMDG (Vessel):  
UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air):  
UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air):  
UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada):  
UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

---

**SECTION 15. REGULATORY INFORMATION**

- TSCA list** : No substances are subject to a Significant New Use Rule.  
No substances are subject to TSCA 12(b) export notification requirements.

**EPCRA - Emergency Planning and Community Right-to-Know Act**

**CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

**SAFETY DATA SHEET**



**A00141 MST STAINLESS STL CLNR/PLSH 20N15**

Version 1.4

Revision Date 02/25/2017

Print Date 02/06/2018

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : Fire Hazard  
Sudden Release of Pressure Hazard  
Acute Health Hazard

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**California Prop 65** This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

**The components of this product are reported in the following inventories:**

**TSCA** On TSCA Inventory  
**DSL** All components of this product are on the Canadian DSL

For information on the country notification status for other regions please contact the manufacturer's regulatory group.


**Inventory Acronym and Validity Area Legend:**

TSCA (USA), DSL (Canada), NDSL (Canada)

**SECTION 16. OTHER INFORMATION**

**Further information**

**NFPA:**



**HMIS III:**

<b>HEALTH</b>	<b>3</b>
<b>FLAMMABILITY</b>	<b>4</b>
<b>PHYSICAL HAZARD</b>	<b>2</b>

0 = not significant, 1 = Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

**OSHA - GHS Label Information:**



# SAFETY DATA SHEET



## A00141 MST STAINLESS STL CLNR/PLSH 20N15

Version 1.4

Revision Date 02/25/2017

Print Date 02/06/2018

Hazard pictograms :



Signal word :

**Danger:**

Hazard statements :

Extremely flammable aerosol. Contains gas under pressure; may explode if heated.  
May cause an allergic skin reaction.

Precautionary statements :

**Prevention:** Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/fume/gas/mist/vapours/spray. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves.  
**Response:** IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.  
**Storage:** Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.  
**Disposal:** Dispose of contents/container in accordance with local regulation.

Version:	1.4
Revision Date:	02/25/2017
Print Date:	02/06/2018

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®, Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®, Rexodan®, Mykal™, and a number of private labeled brands.