



SAFETY DATA SHEET

PRODUCT NAME: 9200 PERMASET SILVER PART A (2A:1B)
PRODUCT CODE: 9200136.

REVISION DATE: 10/30/2018

SECTION 1 - PRODUCT IDENTIFICATION & MANUFACTURER INFORMATION

PRODUCT NAME.....: 9200 PERMASET SILVER PART A (2A:1B)
PRODUCT CODE.....: 9200136.
OTHER MEANS OF IDENTIFICATION: EPOXY
PRODUCT TYPE.....: COATING (BASE COMPONENT OF TWO PART SYSTEM)
RECOMMENDED USES and/or USE RESTRICTIONS: INDUSTRIAL/PROFESSIONAL USE ONLY

COMPANY IDENTIFICATION:

PONDEROSA PAINT CO. dba SURFACE ENGINEERED TECHNOLOGIES
C/O SET MFG PLANT
5626 E. SHIELDS AVE.
FRESNO, CA 93727

INFORMATION PHONE.....: 559 291-0664
EMERGENCY PHONE (CHEMTREC): 800-424-9300

SECTION 2 - HAZARDS IDENTIFICATION

OSHA / HCS STATUS:

THIS MATERIAL IS CONSIDERED HAZARDOUS BY THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200).

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE:

SKIN CORROSION/IRRITATION (CATEGORY 2)
SKIN SENSITIZATION (CATEGORY 1B)
CHRONIC AQUATIC TOXICITY (CATEGORY 2)
ACUTE ORAL/DERMAL TOXICITY (CATEGORY 5)
SERIOUS EYE IRRITATION (CATEGORY 2)

PERCENTAGE OF MIXTURE CONSISTING OF INGREDIENTS OF UNKNOWN TOXICITY:

9%

HAZARD PICTOGRAMS:

HEALTH HAZARD (HEALTH HAZARD)
ENVIRONMENT (ENVIRONMENTALLY DAMAGING)

SIGNAL WORD.....: WARNING!

HAZARDOUS STATEMENTS:

H302: HARMFUL IF SWALLOWED
H315: CAUSES SKIN IRRITATION
H317: MAY CAUSE AN ALLERGIC SKIN REACTION
H319: CAUSES SERIOUS EYE IRRITATION



SAFETY DATA SHEET

PRODUCT NAME: 9200 PERMASET SILVER PART A (2A:1B)

PRODUCT CODE: 9200136.

H411: TOXIC TO AQUATIC LIFE WITH LONG LASTING EFFECTS

GENERAL PRECAUTIONARY STATEMENTS:

PREVENTION:

- P261: AVOID BREATHING DUST/FUME/GAS/MIST/VAPOURS/SPRAY.
- P264: WASH SKIN THOROUGHLY AFTER HANDLING.
- P272: CONTAMINATED WORK CLOTHING SHOULD NOT BE ALLOWED OUT OF THE WORKPLACE.
- P273: AVOID RELEASE TO THE ENVIRONMENT.
- P280: WEAR PROTECTIVE GLOVES/PROTECTIVE CLOTHING/EYE PROTECTION/FACE PROTECTION.

RESPONSE:

- P302 + P352: IF ON SKIN: WASH WITH PLENTY OF WATER/...
- P305 + P351 + P338: IF IN EYES: RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO. CONTINUE RINSING.
- P333 + P313: IF SKIN IRRITATION OR RASH OCCURS: GET MEDICAL ADVICE/ATTENTION.
- P337 + P313: IF EYE IRRITATION PERSISTS: GET MEDICAL ADVICE/ATTENTION.
- P362: TAKE OFF CONTAMINATED CLOTHING.
- P391: COLLECT SPILLAGE.

STORAGE:

- P404: STORE IN A CLOSED CONTAINER.

DISPOSAL:

- P501: DISPOSE OF CONTENTS AND CONTAINER IN ACCORDANCE WITH ALL LOCAL, STATE, AND FEDERAL REGULATIONS.

SUPPLEMENTAL LABEL ELEMENTS:

CAUSES SKIN AND EYE IRRITATION.

HAZARDS NOT OTHERWISE CLASSIFIED:

EVEN THOUGH NO SIGNIFICANT NEGATIVE EXPOSURE IS THOUGHT TO OCCUR WHEN IT IS ENCAPSULATED IN A WET COATING USE ADEQUATE VENTILATION WHEN SANDING OR SCRAPING IT AS A DRIED FILM. PAINT AND COATING FILM MAY CONTAIN CRYSTALLINE SILICA, WHICH WHEN INHALED CAN CAUSE LUNG DISEASE AND POSSIBLY CANCER. TO AVOID BREATHING IN SILICA, WEAR AN APPROPRIATE, PROPERLY FITTED PARTICULATE FILTER RESPIRATOR (NIOSH APPROVED) FOLLOW RESPIRATOR MANUFACTURER'S DIRECTIONS FOR RESPIRATOR USE.

SECTION 3 - COMPOSITION & INFORMATION ON INGREDIENTS

SUBSTANCE / MIXTURE.....: MIXTURE

OTHER MEANS OF IDENTIFICATION (COMPOSITION): NOT AVAILABLE

Component	CAS#	% by Wt.
CASTOR OIL GLYCIDYL ETHER	74398-71-3	10.5
EPOXY DILUENT	17557-23-2	6.2
SILICA, QUARTZ	14808-60-7	.5

THERE ARE NO ADDITIONAL INGREDIENTS PRESENT WHICH, WITHIN THE CURRENT KNOWLEDGE OF THE SUPPLIER AND IN THE CONCENTRATIONS APPLICABLE, ARE CLASSIFIED AS HAZARDOUS TO HEALTH OR THE ENVIRONMENT AND HENCE REQUIRE REPORTING IN THIS



SAFETY DATA SHEET

PRODUCT NAME: 9200 PERMASET SILVER PART A (2A:1B)

PRODUCT CODE: 9200136.

SECTION.

SECTION 4 - FIRST AID MEASURES

EYE CONTACT:

HOLD EYELIDS APART AND IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR 15 MINUTES. SEEK MEDICAL ADVICE. REMOVE CONTACT LENSES.

INHALATION:

MOVE PERSON TO FRESH AIR. GET MEDICAL ATTENTION IF SYMPTOMS DEVELOP.

SKIN CONTACT:

DRENCH THE AFFECTED AREA IMMEDIATELY WITH PLENTY OF WATER; REMOVE CONTAMINATED CLOTHING. WASH THOROUGHLY WITH SOAP AND WATER FOR AT LEAST 15 MINUTES. SEEK MEDICAL ATTENTION IF IRRITATION, RASH OR OTHER ADVERSE EFFECTS OCCUR.

INGESTION:

IN THE EVENT OF SWALLOWING, DO NOT INDUCE VOMITING; RINSE MOUTH THEN DRINK PLENTY OF WATER; GET MEDICAL ATTENTION IF SYMPTOMS PERSIST.

POTENTIAL HEALTH EFFECTS:

SKIN IRRITATION, ALLERGIC REACTIONS.

OVER-EXPOSURE SIGNS / SYMPTOMS:

SKIN IRRITATION, ALLERGIC REACTIONS.

NOTE TO PHYSICIAN:

TREAT SYMPTOMATICALLY.

SECTION 5 - FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA:

DRY CHEMICAL, CO2, WATER FOG/MIST, FOAM

UNSUITABLE EXTINGUISHING MEDIA:

WATER FULL JET

HAZARDOUS COMBUSTION PRODUCTS:

CARBON MONOXIDE, CARBON DIOXIDE, PHENOLICS, SMOKE MAY CONTAIN PARTICLES OF THE ORIGINAL MATERIAL AS WELL.

OTHER CONSIDERATIONS:

EXPOSURE TO DECOMPOSITION PRODUCTS MAY BE HARMFUL TO HEALTH. PREVENT FIRE FIGHTING WATERS FROM ENTERING SEWER OR WATERWAYS.

FIRE FIGHTING PROCEDURES:

DO NOT USE HIGH VOLUME WATER JET AS THIS MAY SPREAD THE AREA OF THE FIRE.



SAFETY DATA SHEET

PRODUCT NAME: 9200 PERMASET SILVER PART A (2A:1B)

PRODUCT CODE: 9200136.

FIRE FIGHTING EQUIPMENT:

WEAR FULL PROTECTIVE GEAR AND SCBA.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTION:

ISOLATE AREA; ENSURE ADEQUATE VENTILATION; USE APPROPRIATE PERSONAL PROTECTION EQUIPMENT; AVOID BREATHING MIST, VAPORS, AND SPRAY; AVOID CONTACT WITH SKIN, EYES AND CLOTHING; KEEP UNNECESSARY AND UNPROTECTED PERSONNEL FROM ENTERING THE INVOLVED AREA.

ENVIRONMENTAL PRECAUTIONS:

PREVENT CONTAMINATION OF SOIL AND WATER. PREVENT FROM SPREADING OR ENTERING INTO DRAINS, DITCHES, AND WATERWAYS BY USING SAND EARTH OR APPROPRIATE BARRIERS.

METHODS FOR CONTAINMENT & CLEAN-UP:

ABSORB WITH SAND, DIATOMACEOUS EARTH OR UNIVERSAL BINDERS AND COLLECT INTO SUITABLE DISPOSAL CONTAINER. DISPOSE OF IN ACCORDANCE WITH APPLICABLE LOCAL AND FEDERAL ENVIRONMENTAL CONTROL LAWS AND REGULATIONS.

SECTION 7 - HANDLING & STORAGE

PROTECTIVE MEASURES FOR HANDLING:

ENSURE ADEQUATE VENTILATION OF WORKPLACE AND STORAGE AREAS. AVOID SKIN CONTACT. DO NOT BREATHE MIST, VAPORS OR SPRAY. USE RECOMMENDED PERSON PROTECTIVE EQUIPMENT. AVOID USE OF ELECTRIC BAN HEATERS AS FAILURE OF SUCH HEATERS HAS BEEN REPORTED TO CAUSE CONTAINERS OF LIQUID EPOXY RESINS TO EXPLODE AND CATCH FIRE. NEVER APPLY A DIRECT FLAME TO ANY CONTAINER OF PRODUCT.

ADVICE ON GENERAL OCCUPATIONAL HYGIENE:

WEAR APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT. USE GENERAL INDUSTRIAL HYGIENE PRACTICE. WASH HANDS AFTER HANDLING PAINT/COATING AND BEFORE EATING, DRINKING OR SMOKING. READ AND UNDERSTAND ENTIRE SDS BEFORE HANDLING PRODUCT.

CONDITIONS FOR SAFE STORAGE (INCLUDING ANY INCOMPATIBILITIES):

STORE IN A COOL, DRY, WELL VENTILATED PLACE. KEEP AWAY FROM INCOMPATIBLE MATERIALS: STRONG OXIDIZING AGENTS, ACIDS, ALKALIS, AMINES, MECAPTANS. KEEP CONTAINER TIGHTLY CLOSED. RECOMMENDED STORAGE TEMPERATURE IS 50 TO 95°F.

SECTION 8 - EXPOSURE CONTROLS & PERSONAL PROTECTION

AIRBORNE EXPOSURE LIMITS:

CASTOR OIL GLYCIDYL ETHER	74398-71-3	10.5
ACGIH/TLV : N/E		
OSHA/PEL : N/E		
EPOXY DILUENT	17557-23-2	6.2
ACGIH/TLV : N/E		



SAFETY DATA SHEET

PRODUCT NAME: 9200 PERMASET SILVER PART A (2A:1B)

PRODUCT CODE: 9200136.

OSHA/PEL : N/E
 SILICA, QUARTZ 14808-60-7 .5
 ACGIH/TLV : 0.025 mg/m3 TWA
 OSHA/PEL : 0.1 mg/m3 TWA Respirable

ENGINEERING CONTROLS:
USE WITH ADEQUATE VENTILATION.

PERSONAL PROTECTIVE EQUIPMENT

RESPIRATORY PROTECTION:

ALTHOUGH NO EXPOSURE LIMITS HAVE BEEN ESTABLISHED, RESPIRATORY PROTECTION MAY BE WORN IF ANY RESPIRATORY IRRITATION OR DISCOMFORT IS NOTED. IF USING A RESPIRATOR FOLLOW RESPIRATOR MANUFACTURER'S DIRECTIONS FOR RESPIRATOR USE.

SKIN & BODY PROTECTION:

IMPERVIOUS CHEMICAL RESISTANT GLOVES. LONG SLEEVED CLOTHING OR PROTECTIVE SLEEVES. REMOVE AND WASH CONTAMINATED CLOTHING BEFORE RE-USE.

EYE & FACE PROTECTION:

SPLASH PROOF SAFETY GLASSES

WORK HYGIENIC PRACTICES:

WASH HANDS, FOREARMS AND FACE THOROUGHLY AFTER HANDLING CHEMICAL PRODUCTS, BEFORE EATING AND DRINKING, SMOKING OR USING THE LAVATORY AND AT THE END OF THE WORKING PERIOD. CONTAMINATED WORK CLOTHING SHOULD NOT BE ALLOWED WORN OUT OF THE WORKPLACE. WASH CONTAMINATED CLOTHING BEFORE REUSING. ENSURE THAT EYEWASH STATIONS AND SAFETY SHOWERS ARE CLOSE TO THE WORKSTATION LOCATION.

SECTION 9 - PHYSICAL & CHEMICAL PROPERTIES

PHYSICAL STATE:

APPEARANCE.....: LIQUID
 COLOR.....: VARIOUS COLORS
 ODOR.....: FAINT EPOXY ODOR
 ODOR THRESHOLD.....: NOT AVAILABLE
 pH.....: NOT APPLICABLE
 MELTING POINT.....: NOT AVAILABLE
 FREEZING POINT.....: NOT AVAILABLE
 INITIAL BOILING POINT.....: NOT AVAILABLE
 FLASH POINT.....: >212°F
 EVAPORATION RATE.....: NOT AVAILABLE
 EXPLOSION LIMITS:
 LOWER & UPPER EXPLOSIVE LIMIT.....: NOT AVAILABLE
 VAPOR PRESSURE.....: NOT AVAILABLE



SAFETY DATA SHEET

PRODUCT NAME: 9200 PERMASET SILVER PART A (2A:1B)
PRODUCT CODE: 9200136.

VAPOR DENSITY (Air = 1).....: NOT AVAILABLE
SPECIFIC GRAVITY (g/cc).....: 1.42
DENSITY (lb/gal).....: 11.86 lb/gl
SOLUBILITY IN WATER.....: NIL
PARTITION COEFFICIENT.....: NOT AVAILABLE
(n-Octanol / Water)
VISCOSITY.....: 1,200 - 2,000 cps.
AUTO-IGNITION TEMPERATURE....: NOT AVAILABLE
DECOMPOSITION TEMPERATURE....: NOT AVAILABLE
ACTUAL V.O.C.....: 0.145 lb/gl
(Metric).....: 17 g/l
REGULATORY V.O.C.....: 0.145 lb/gl
(Metric).....: 17 g/l
OTHER PHYSICAL PROPERTIES....: NOT AVAILABLE

SECTION 10 - STABILITY & REACTIVITY

CHEMICAL STABILITY.....:
STABLE UNDER NORMAL CONDITIONS

POSSIBLE HAZARDOUS REACTIONS.:
HAZARDOUS REACTIONS WILL NOT OCCUR UNDER NORMAL CONDITIONS. HOWEVER, MASSES OF MORE THAN ONE POUND PLUS AN ALIPHATIC AMINE WILL CAUSE IRREVERSIBLE POLYMERIZATION WITH CONSIDERABLE HEAT BUILD-UP. MATERIAL WILL POLYMERIZE WITH SODIUM HYDROXIDE.

CONDITIONS TO AVOID:
AVOID ELEVATED TEMPERATURES. VIOLENT DECOMPOSITION CAN OCCUR ABOVE 662°F.

INCOMPATIBLE MATERIALS.....:
STRONG OXIDIZING AGENTS, ACIDS, ALKALIS, AMINES, MERCAPTANS.

HAZARDOUS DECOMPOSITION.....:
UNCONTROLLED EXOTHERMIC REACTION OF EPOXY RESIN RELEASES CARBON MONOXIDE, CARBON DIOXIDE, PHENOLICS.

SECTION 11 - TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS

ACUTE TOXICITY:
THE ACUTE EFFECTS OF THIS PRODUCT AS A WHOLE HAVE NOT BEEN TESTED.
DATA ON INDIVIDUAL COMPONENTS ARE BELOW:

EPOXY RESIN (25068-38-6)
LD50 ORAL RAT >5,000 mg/kg
LC50 INHALATION RAT NO DATA AVAILABLE
LD50 DERMAL RABBIT 20,000 mg/kg

CASTOR OIL DIGLYCIDYL ETHER (74398-71-3)



SAFETY DATA SHEET

PRODUCT NAME: 9200 PERMASET SILVER PART A (2A:1B)

PRODUCT CODE: 9200136.

LD50 ORAL RAT >5,000 mg/kg
LC50 INHALATION RAT NO DATA AVAILABLE
LD50 DERMAL RABBIT >2,000 mg/kg

NEOPENTYL GLYCOL DIGLYCIDYL ETHER (17557-23-2)
LD50 ORAL RAT 4,500 mg/kg
LC50 INHALATION RAT NO DATA AVAILABLE
LD50 DERMAL RABBIT >2,100 mg/kg

THE ACUTE EFFECTS OF THIS PRODUCT AS A WHOLE HAVE NOT BEEN TESTED.
DATA ON INDIVIDUAL COMPONENTS ARE BELOW:

CRYSTALLINE SILICA (14808-60-7)
LD50 ORAL RAT >22,500 mg/kg
LC50 INHALATION RAT NO DATA
LD50 DERMAL RABBIT NO DATA

CARCINOGENICITY:

CONTAINS AN INGREDIENT THAT IS A SUSPECTED CARCINOGEN. SEE BELOW.

OSHA:

CONTAINS CRYSTALLINE SILICA, WHICH IN DUST FORM, MAY CAUSE CANCER.

IARC:

TITANIUM DIOXIDE IS CONSIDERED POSSIBLY CARCINOGENIC TO HUMANS (GROUP 2B) BY IARC. IARC CLASSIFIES CRYSTALLINE SILICA A GROUP 1 CARCINOGEN.

NTP:

THE NATIONAL TOXICOLOGY PROGRAM CLASSIFIES CRYSTALLINE SILICA WHEN DUST TO BE A KNOWN HUMAN CARCINOGEN.

EFFECTS OF ACUTE EXPOSURE FROM EYE CONTACT:

MAY CAUSE SKIN AND EYE IRRITATION.

EFFECTS OF ACUTE EXPOSURE FROM SKIN CONTACT:

MAY BE ABSORBED THROUGH THE SKIN. MAY CAUSE SENSITIZATION, DERMATITIS. MAY CAUSE ALLERGIC REACTIONS IN SENSITIVE INDIVIDUALS. PROLONGED OR REPEATED SKIN CONTACT CAN CAUSE DEFATTING AND DRYING OF THE SKIN WHICH MAY RESULT IN A BURNING SENSATION AND A DRIED CRACKED APPEARANCE.

EFFECTS OF ACUTE EXPOSURE FROM INGESTION:

MAY CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING, DIARRHEA. MATERIAL IS LOW IN TOXICITY BUT IRRITATING TO THE MUCOUS MEMBRANES.

EFFECTS OF ACUTE EXPOSURE FROM INHALATION:

MAY CAUSE NOSE, THROAT, AND LUNG IRRITATION. INHALATION OF HIGH CONCENTRATIONS OF VAPORS OR AEROSOLS MAY IRRITATE THE RESPIRATORY TRACT.

EFFECTS OF CHRONIC EXPOSURE:



SAFETY DATA SHEET

PRODUCT NAME: 9200 PERMASET SILVER PART A (2A:1B)

PRODUCT CODE: 9200136.

PROLONGED OR REPEATED SKIN CONTACT CAN CAUSE DEFATTING AND DRYING OF THE SKIN WHICH MAY RESULT IN A BURNING SENSATION AND A DRIED CRACKED APPEARANCE.

PRIMARY ROUTE(S) OF ENTRY:

EYE CONTACT, SKIN CONTACT, INGESTION, INHALATION

SECTION 12 - ECOLOGICAL INFORMATION

ENVIRONMENTAL TOXICITY:

ECOLOGICAL EVALUATION OF THIS MATERIAL HAS NOT BEEN PERFORMED; HOWEVER, DO NOT ALLOW THE PRODUCT TO BE RELEASED TO THE ENVIRONMENT WITHOUT GOVERNMENTAL APPROVAL/PERMITS. DISCHARGE INTO THE ENVIRONMENT MUST BE AVOIDED.

SECTION 13 - DISPOSAL CONSIDERATIONS

DISPOSAL METHOD:

THE GENERATION OF WASTE SHOULD BE AVOIDED OR MINIMIZED WHENEVER POSSIBLE. DISPOSAL OF THIS PRODUCT SHOULD ALWAYS COMPLY WITH THE REQUIREMENTS OF ENVIRONMENTAL PROTECTION AND WASTE DISPOSAL LEGISLATION AND ANY REGIONAL LOCAL AUTHORITY REQUIREMENTS. DISPOSE OF SURPLUS AND NON-RECYCLABLE PRODUCTS VIA A LICENSED WASTE DISPOSAL CONTRACTOR. THE MATERIAL AND ITS CONTAINER MUST BE DISPOSED OF IN A SAFE WAY. CARE SHOULD BE TAKEN WHEN HANDLING EMPTIED CONTAINERS THAT HAVE NOT BEEN CLEANED OR RINSED OUT. EMPTY CONTAINERS MAY RETAIN SOME PRODUCT RESIDUES. AVOID DISPERSAL OF SPILLED MATERIAL AND RUNOFF AND CONTACT WITH SOIL, WATERWAYS, DRAINS, AND SEWERS.

SECTION 14 - TRANSPORTATION INFORMATION

TRANSPORTATION INFORMATION DISCLAIMER:

DETERMINATION OF PROPER SHIPPING IDENTIFICATION IS DEPENDENT UPON THE FORM, QUANTITY AND PACKAGING. THE PERSON OFFERING A HAZARDOUS MATERIAL FOR TRANSPORT HAS THE SOLE RESPONSIBILITY TO PROPERLY PREPARE THE SHIPPING PAPER AND PACKAGING FOR TRANSPORT. PEOPLE LOADING AND UNLOADING MUST BE TRAINED ON ALL OF THE RISKS DERIVING FROM HANDLING THIS PRODUCT.

SECTION 15 - REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS :

CLEAN AIR ACT SECTION 112(b) HAZARDOUS AIR POLLUTANTS (HAP's) :

NO COMPONENTS PRESENT AT LEVELS HIGHER THAN 1% LISTED ON HAPS LIST OF CHEMICALS

CERCLA: SARA Hazard Category:

THIS PRODUCT HAS BEEN REVIEWED ACCORDING TO THE EPA "HAZARD CATEGORIES" PROMULGATED UNDER SECTION 311 AND 312 OF THE SUPERFUND AMENDMENT AND REAUTHORIZATION ACT OF 1986 (SARA TITLE III) AND IS CONSIDERED, UNDER APPLICABLE DEFINITIONS, TO MEET THE FOLLOWING CATEGORIES: ACUTE HEALTH HAZARD.

EPA SECTION 313:

THIS MATERIAL DOES NOT CONTAIN ANY CHEMICAL COMPONENT WITH KNOWN CAS NUMBERS THAT EXCEED THE THRESHOLD (DE MINIMIS) REPORTING LEVELS ESTABLISHED BY SARA TITLE III, SECTION 313:

US STATE REGULATIONS:

CALIFORNIA PROPOSITION 65:



SAFETY DATA SHEET

PRODUCT NAME: 9200 PERMASET SILVER PART A (2A:1B)

PRODUCT CODE: 9200136.

WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

SECTION 16 - OTHER INFORMATION

HMIS RATINGS:

HEALTH.....: 2

FLAMMABILITY...: 1

PHYSICAL HAZARD: 0

ABBREVIATIONS & ACRONYMS:

ACA - AMERICAN COATINGS ASSOCIATION
ACGIH - AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS
ATE - ACUTE TOXICITY ESTIMATE
BCF - BIOCONCENTRATION FACTOR
CAS - CHEMICAL ABSTRACTS SERVICE (DIVISION OF THE AMERICAN CHEMICAL SOCIETY)
CLP - REGULATION (EC) NO 1272/2008 ON CLASSIFICATION, LABELING AND PACKAGING OF SUBSTANCES AND MIXTURES
DOT - US DEPARTMENT OF TRANSPORTATION
EC - EUROPEAN COMMUNITY
EEC - EUROPEAN ECONOMIC COMMUNITY
EINECS - EUROPEAN INVENTORY OF EXISTING COMMERCIAL CHEMICAL SUBSTANCES
EN - EUROPEAN STANDARD
EPA - ENVIRONMENTAL PROTECTION AGENCY (USA)
EU - EUROPEAN UNION
GHS - GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELING OF CHEMICALS
HMIS - HAZARDOUS MATERIALS IDENTIFICATION SYSTEM (USA)
HSDB - HAZARDOUS SUBSTANCES DATA BANK
IARC - INTERNATIONAL ASSOCIATION OF RADIO CARDIOLOGISTS
IATA - INTERNATIONAL AIR TRANSPORT ASSOCIATION
IBC - INTERMEDIATE BULK CONTAINER
ICAO - INTERNATIONAL CIVIL AVIATION ORGANIZATION
IMDG - INTERNATIONAL MARITIME CODE FOR DANGEROUS GOODS
LC - LETHAL CONCENTRATION
LD - LETHAL DOSE
LOLI - LIST OF LISTS
NA - NOT APPLICABLE
ND - NO DATA OR INFORMATION AVAILABLE
NE - NOT ESTABLISHED
NFFPA - NATIONAL FIRE PROTECTION ASSOCIATION (USA)
NTP - NATIONAL TOXICOLOGY PROGRAM (USA)
OECD - ORGANIZATION FOR ECONOMIC CO-OPERATION AND DEVELOPMENT
OEL - OCCUPATIONAL EXPOSURE LIMITS
OSHA - OCCUPATIONAL SAFETY & HEALTH ADMINISTRATION (USA)
RID - REGULATIONS CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY RAIL
RTECS - REGISTRY OF TOXIC EFFECTS OF CHEMICAL SUBSTANCES
RTK - RIGHT-TO-KNOW LAWS
SDS - SAFETY DATA SHEET
STEL - SHORT-TERM EXPOSURE LIMIT
TWA - TIME WEIGHTED AVERAGE
UN - UNITED NATIONS
WEL - WORKPLACE EXPOSURE LIMIT

MANUFACTURER DISCLAIMER:

THE INFORMATION PROVIDED HEREIN WAS BELIEVED BY PONDEROSA PAINT CO., INC.



SAFETY DATA SHEET

PRODUCT NAME: 9200 PERMASET SILVER PART A (2A:1B)

PRODUCT CODE: 9200136.

("PPC") TO BE ACCURATE AT THE TIME OF PREPARATION FROM SOURCES BELIEVED TO BE RELIABLE, BUT IT IS THE RESPONSIBILITY OF THE USER TO INVESTIGATE AND UNDERSTAND OTHER PERTINENT SOURCES OF INFORMATION, TO COMPLY WITH ALL LAWS AND PROCEDURES APPLICABLE TO THE SAFE HANDLING AND USE OF THE PRODUCT AND TO DETERMINE THE SUITABILITY OF THE PRODUCT FOR IT'S INTENDED USE. ALL PRODUCTS SUPPLIED BY PPC ARE SUBJECT TO PPC'S TERMS AND CONDITIONS OF SALE. PPC MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY PPC, EXCEPT THAT THE PRODUCT SHALL CONFORM TO PPC'S SPECIFICATIONS. NOTHING CONTAINED HEREIN CONSTITUTES AN OFFER FOR THE SALE OF ANY PRODUCT.